

## Ethylene Propylene Diene Terpolymer

KUMHO POLYCHEM

### Product Data Sheet

Product Description	Features
KEP5770 is an EPDM rubber with narrow molecular weight distribution, high ethylene contents, medium ENB contents. It can be used to heat resistant hoses, washing machine hoses, window seals and automobile parts.	<ul style="list-style-type: none"><li>- High loadability</li><li>- Excellent extrudability</li><li>- High green strength</li></ul>

Test items	Sale Specifications	Unit	Test Method
Volatile Matter	Max 1.00	wt %	ASTM D5668
Mooney Viscosity ML(1+4)@125 °C	73.0 ± 5.0	MU	ASTM D1646
Ethylene Contents	74.0 ± 2.0	wt %	ASTM D3900
ENB Contents	5.0 ± 0.5	wt %	ASTM D6047

### Other Products Features

<b>Product Form</b>	Bale
<b>Packaging</b>	25 kg/Bale in Carton/Mesh Box, LDPE film, 750 kg(25 kg × 30), 600kg(25 kg X 24, Pad)
<b>Shelf Life</b>	24 months from date of production at room temperature in dry condition, exposure to light has to be avoided
<b>The Others</b>	RoHS Free

### Contact Information

<b>Head Office</b>	8F, East Wing, Signature Tower, #100 Cheonggyecheon-ro, Jung-gu, Seoul, Korea 82-2-6961-0000
<b>Plant</b>	613 Sandanjungang-ro, Yeosu, Jeonnam, Korea 82-61-688-2822
<b>Revision Date</b>	12/02/2020
<b>Revision No.</b>	12